

TECHNICAL DATA SHEET

Edition 26 April 2017

GALVANISED ZINC FILM
CORROSION PROTECTION
QUICK DRYING

TIGER EASY BOND FOR MASONRY ADHESIVE

DESCRIPTION

Tiger Easy Bond for Masonry Adhesive is a rapid curing PU foam adhesive developed specifically for the installation of brick, stone, block and a range of other construction materials.

USES

- Ideal for bonding and setting of Brickworks, Breeze Blocks, Natural Stone, Aerated Concrete and Granite etc.
- No mixing, no water, no power, no Mess, no waste: No need to spend time mixing sand and cement.
- It takes seconds to apply, and sets within minutes. This is real alternative to mortar.

FEATURE

- easy of use
- strong bonding
- good adhesion on many surfaces
- able to apply at low temperatures
- immediate use, no mixing required
- no water or electricity required



TIGER EASY BOND FOR ALC

PRODUCT INFORMATION

- Packaging: 750ml canister(15 cans per box)
- Store in shaded dry conditions between +10 °C and +25 °C
- Canisters must be stored upright.

PROPERTIES

Base	Polyurethane
Curing System	Moisture curing
Tack Free Time	8 min at 20°C/50% R.H
Full Cure Time	Ca. 24 hour at 20°C/50% R.H
Temperature Resistance	-40°C ~ 100°C (cured)
Coverage(1 can)	Ca. 28 pcs of 150T ALC blocks applied in 2 bond lines
Compressive Strength	Ca. 9.0N / mm ² (Korea Testing & Research Institute)

DIRECTIONS FOR USE

- To begin, screw the canister firmly onto the applicator gun. Shake the canister vigorously prior to use at least 20 times.
- Extrude the foam carefully by applying pressure on the trigger. Shake canister regularly during the application.
- Apply the bead along the horizontal and vertical sections to be bonded
- TIGER Easy Bond for Masonry adhesive cures within 10 -15 minutes, and is fully load bearing within 24 hours.

